



enUS

**Hatz Energy Solutions** 

# GD 3200 Silent Pack: Features and Benefits

- Ideal for RV OEM first fit applications
- Computer-controlled constant speed operation -quiet diesel performance for smaller RVs
- Special sound-controlling housing encloses cooling system and muffler
- Double isolation mounting system reduces vibration
- Easy, accessible maintenance points
- Runs one rooftop air conditioner with powerto spare
- Integrated start/stop control with hour meter

# Ambient conditions for rated output with muffler and RV enclosure, per ISO 8528-1:

Temperature: 77°F (25°C)

**Altitude:** 500 ft [152.4 mm],[99 kPa dry]

#### Power output change based on ambient conditions:

 $\textbf{Temperature:} \ \mathsf{Power} \ \mathsf{output} \ \mathsf{decreases} \ 1\% \ \mathsf{for} \ \mathsf{every}$ 

10°F (5.5°C) increases

Altitude: Power output decreases 3.5% for every

1000 ft (305 mm) increases.

Ratings represent minimums. Actual performance may be significanlty higher based on installation and operating conditions.

#### **Battery Chargers**

Designed specifically to charge batteries by converting diesel fuel into electrical energy, providing a portable and efficient solution for recharging batteries with direct current.

#### **Generators**

Produces continuous electrical power to supply a broad range of devices and systems, like recreational vehicles [RV] with alternating current.

Weight: 205 lbs. [93kg] Length: 30.2 in. [766mm] Width: 17.3 in. [439mm] Height: 18 in. [453mm]

**Sound Level:** 72 dB[A] (reading at 10ft (3m) half load) Meets national park service sound level requirements [60 dB[A] @ 50 ft) for national park use. Typical installation will further reduce sound level.

Design: Hatz 4-cycle, air-cooled diesel engine

**Cylinders:** 1, vertical **Bore:** 3.15 in [80.0mm] **Stroke:** 2.72 in [69mm]

**Displacement:**  $21.16 \text{ in}^3 (347 \text{ cm}^3)$ 

Compression ratio: 22 to 1 Lube oil capacity: 1.2 qt [1.1L]

#### **Control Systems**

- Microprocessor control
- Service diagnostics
- Maintenance reminders
- Over voltage, over speed and overload safety
- AC alternator over temp safety
- Automatic timed glow plug
- Remote LCD display with start/stop switches included
- Remote display harness included-26.2 ft (8 m)

#### **Standard Features**

- Hatz single cylinder diesel engines
- Hatz fiPMG (Flywheel Integrated Permanent Magnet Generator)
- Digital voltage regulation with no adjustment required
- Integral enclosed muffler with stationary exhaust pipe connection point
- USDA-approved spark arrestor
- Sound insulated cover with cooling air inlet and outlet ducts
- Heavy-duty air cleaner
- Automotive type starter
- Hour meter
- Meets applicable U.S. EPA and California emissions standards
- Connector for remote operation
- Double isolation mounting system
- Terminal block connection for AC output
- · Electric fuel pump
- Fuel filter
- Cleanable oil screen filter
- Service and maintenance through service doors
- Pure sine wave

#### **Testing for RV Applications**


- Tested at extreme temperatures -20°F (-29°C) to 120°F (49°C) for starting and operation
- Tested with RV loads, air conditioners, microwaves, converter, TVs, VCRs
- Tested in high humidity conditions
- Tested in salt spray conditions
- Tested in heavy airborne dust conditions
- Field test program
- 60 Hz (120 V only) models listed by SGS U.S.


# Testing Company, Inc per ANSI/RVIA EGS-1 and CSA-certified by Std. 100 motors and generators and TIL RV 06.


- This generator set was designed and manufactured in facilities certified to ISO 9001
- 60 Hz models meet applicable U.S. EPA and California emissions standards

### Technical Data [mm (in)]

Model	Frequency	Watts	Voltage	Amps	Phase
GD 3200-120 Silent Pack RV	60 Hz	3200	120	26.7	1
BD 2800-28 Silent Pack	60 Hz	2800	28	100	1
BD 3000-56 Silent Pack	60 Hz	3000	56	56	1







## Fuel Consumption Gal/h(L/h)

No Load	Half	Full load	
0.2 Gal/h (0.7 L/h)	0.3 Gal/h (1.0 L/h)	0.4 Gal/h (1.4 L/h)	

#### **WARNING:**

Back feed to a utility system can cause electrocution and/or property damage. Do not connect to any building electrical except through an approved device or after building main breaker is open.

#### ! WARNING:

Do not use this generator set on a boat. Such use may violate U.S. Coast Guard regulations, and can result in severe personal injury or death from fire, explosion, electrocution, or carbon monoxide poisoning.

Hatz Americas, Inc. W229 N1645 Westwood Drive Waukesha WI 53186-1153 United States of America Phone +1 [262] 544 0254 hatzamericas.com

After Sales Support



network.hatz-diesel.com



ENUS 02.24 Printed in US We reserve the right to make all changes that serve technical development.